

HOT STAMPING MACHINE: ATP200S

For lipsticks, mascara bottles, caps



AUTOMATIC LIPSTICK HOT STAMPING MACHINE

With the new technology, the machine have three axis driven by servo motor, six stations precision indexing table, before decorating position-setting, touch screen for all parameters setting.

Machine Specifications

Hot Plate Size	L120 x W 100 mm
Tube Size	Φ9-30mm x L90mm
Temperature	Max399 deg C digital setting
Position accuracy	radial: ±0.25mm
Normal Speed	30-45/Min for Dia18mm and 360deg decorate
Power supply	200~230V, 50/60 Hz. single Phase
Heater Consumption	1.2KW
Power Consumption	2.0KW
Air Pressure	5 to 10 bar
Dimension	L1250mm x W1150mm x H1750mm
Weight	500 Kg

Stand and Features

- PLC and Touch Screen
- three Axis driven by Servo Motor
- Loading conveyor/output conveyor
- Positioning before decorating
- Digital Temperature controller
- Foil feeding by Ac speed Motor, two system optional.

Quality Guarantee

- 1: one year free service for manufacture defect
- 2: two years electrical parts warranty
- 3: life-time service

Contact: GT AUTOMATION
Blk 512 Chai Chee Lane #03-04,
Singapore 469028
Mr: Sui Guo Tai
TEL: 65-97765198 Fax: 65-67027650
Email: guot99@singnet.com.sg
www.sgtautomation.com

Made in Singapore